



Tailored ventilation

Philips Respironics BiPAP A40 - because every patient is different

Because our innovations are inspired by you and your patients, the bi-level ventilator BiPAP A40 has been designed to combine ease-of-use and comfort with technological innovations that adapt to your patient's condition to deliver enhanced therapy.

Based on a familiar platform, BiPAP A40 comes with well-known and clinically proven Philips Respironics technology such as Auto-Trak, AVAPS and a Dry Box humidifier design. The device is capable of non-invasive and invasive pressure ventilation, up to 40 cmH₂O, providing treatment for your patients with chronic respiratory insufficiency.

BiPAP A40 can provide autonomy and increased support to patients, thanks to its specially designed battery module.

The device features AVAPS-AE, an innovative mode of ventilation designed to help clinicians during titration process, while maintaining comfort and therapy optimization. This new ventilation mode helps in providing long-term therapy compliance, regardless of changes to the body position, sleep stages and respiratory mechanics.

PHILIPS

RESPIRONICS

sense and simplicity

AVAPS-AE mode

In AVAPS-AE mode, the device monitors the patient's upper airway resistance and automatically adjusts the delivered EPAP required to maintain a patent airway. Simultaneously, BiPAP A40 automatically adjusts pressure support to maintain a target tidal volume, and when the breath rate is set to Auto, the device will adjust the back-up breath rate based on the patient's spontaneous respiratory rate.

Ordering information

Devices	Part no.
BiPAP A40, International *	1076493
BiPAP A40, Australia *	1076583

* contains BiPAP A40 ventilator with SD card, power cord, AC power adapter, user manual, ultra fine filter, grey foam filter, tubing, and carrying case

Accessories

A Series humidifier, International	1077107
Battery module	1096770
Detachable battery	1043570
Ultra fine filter kit	1063096
Foam filter kit	1063091
Power supply	1081167
Power cord, Europe	1039014
Power cord, UK	1039026
Performance tubing 22 mm	1032907
Performance tubing 15 mm	1074400
EncorePro 2 software	1054785
DirectView software	1005297
RJ9 to 1/4" nurse call cable, closed	1080247
RJ9 to 1/4" nurse call cable, open	1080248
RJ9 nurse call cable, open ends	1080249
Carrying bag	1098514
BiPAP A40 in-use bag	1098513
Oximetry accessory, INTL	100215E
BiPAP A Series roll stand	1098538

Product specifications

Ventilation modes	• CPAP • S • S/T • PC • T • AVAPS-AE
Hybrid ventilation	• AVAPS (Average Volume Assured Pressure Support) • AVAPS-AE
IPAP	4 – 40 cmH ₂ O
EPAP	4 – 25 cmH ₂ O
Target tidal volume (AVAPS & AVAPS-AE)	200 – 1500 ml
Breath rate	0 – 40 bpm (4 – 40 bpm in T mode)
Inspiratory time	0.5 – 3 sec.
Triggering and cycling	• Auto-Trak • Sensitive Auto-Trak • Flow triggering
Rise time	1 (100 ms) – 6 (600 ms)
Size	21.6 cm W x 19 cm L x 11.5 cm H
Weight	2.1 kgs (with power supply)
Noise level	< 30 dBA at 10 cmH ₂ O
Humidification	System One humidity control and 'Dry Box' technology
Alarms	• Patient disconnection • Apnea • Low minute ventilation • Low tidal volume (with AVAPS/AVAPS-AE only) • High respiratory rate
Monitoring	• Pressure • Tidal volume • Minute ventilation • Respiratory rate • Leak • I/E ratio
Battery back up	Detachable battery module: 5 hours at IPAP 12 cmH ₂ O / EPAP 7 cmH ₂ O and 12 bpm
DC power source	• 12 VDC, 5.0 A (external battery) • 24 VDC, 4.2 A (power supply)
Data management	• EncorePro 2 and DirectView software • Compatible with oximetry module • Advanced detection of residual respiratory events (apnea/hypopnea index, obstructed airway apnea, clear airway apnea, hypopnea, periodic breathing, RERA, large leak and snore)
Remote control	Compatible with PC Direct
Polygraph and polysomnograph connections	• Direct connection to Alice PDx and Alice6 PSGs • AOM to connect to most PSG systems

BiPAP A40, Auto-Trak, AVAPS, AVAPS-AE, EncorePro, DirectView, and Alice are trademarks of Koninklijke Philips Electronics N.V. All rights are reserved.

Please visit www.philips.com/respironics



© 2012 Koninklijke Philips Electronics N.V. All rights are reserved.

Philips Healthcare reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Broudy AE 9/12/12 MCI 4105036 PN 1102086

Philips Healthcare is part of Royal Philips Electronics

Philips Respironics International Headquarters
+33 1 47 28 30 82
Philips Respironics Asia Pacific
+65 6882 5282
Philips Respironics Australia
+61 (2) 9947 0440
Philips Respironics United Kingdom
+44 800 1300 845

Philips Respironics
1010 Murry Ridge Lane
Murrysville, PA 15668 USA

Customer Service
+1 724 387 4000
800 345 6443 (toll free, US only)
www.philips.com/respironics